



Scapa 4405

General Purpose u-PVC Double Sided Tape

DESCRIPTION

Scapa 4405 is a general purpose double sided tape based on a UPVC film. The tape is coated on both sides with a solvent rubber based adhesive system with an 82gr. white siliconised paper release liner, resulting in a total thickness of 0.10 mm. Recommended for general purpose bonding, mounting and splicing applications.

APPLICATIONS

- General purpose splicing tape except for siliconised films and papers.
- Mounting display items.
- Mounting dummy pack.
- Mounting sample cards.
- Show card assembly.

PRODUCT BENEFITS

- Clean removal after use.
- High tack.
- Not recommended for direct exposure to sunlight or UV.
- Service temperature: -10°C to +70°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness (Without Liner)	100	µm	AFERA 5006
Tensile Strength	60	N/cm	AFERA 5004
Liner Thickness	69	µm	AFERA 5006
Elongation at Break	75	%	AFERA 5004
Adhesion to Steel	12	N/25mm	AFERA 5001

Version: 1

Date: 14/06/2016

Page: 1 of 2

www.scapa.com

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

- Roll Width: 12, 19, 25, 50, 100 and 1,355 mm
- Roll Width: 33 metres
- Packaging: Plastic bags
- Core: 76mm Scapa branded cardboard
- Colours: Translucent

Note:

Note: Other dimensions are available upon request and subject to minimum order quantities.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants